

Canon imageRUNNER 2520

Karakteristike

- Print, kopiranje, skeniranje i opcionalni i-Send i faks
- Do 20 str/min, 6.4 sekundi do prve kopije
- do 2,000 listova maksimalnog kapaciteta papira
- Kompaktni dizajn i intuitivni ekran osjetljiv na dodir
- Široki raspon konfiguracijskih opcija
- Energetski efikasan

Osnovne karakteristike	
Tip	Stolni ili samostojeći
Maksimalna veličina originala	A3
Veličine kopiranja	Kazeta 1,3 i 4: A3, A4, A4R, A5R Nestandardne veličine: 139.7 do 297mm x 182 do 432mm Kazeta 2: A3, A4, A4R, A5R, Omotnice (uz opcionalni Envelope Feeder Attachment-D1) Direktno umetanja: A3, A4, A4R, A5R, Omotnice Nestandardne veličine: 99 do 297mm x 148 do 432 mm
Rezolucija	Skeniranje: 600dpi x 600dpi Kopiranje: 600dpi x 600dpi Ispis: 600dpi x 600dpi, 1200dpi x 1200dpi (samo uz UFR II-LT) Broj sivih tonova: 256
Brzine kopiranja/ispisa	A4: imageRUNNER 2545i/2545 : 45 str/min (CB) imageRUNNER 2535i/2535 : 35 str/min (CB) imageRUNNER 2530i/2530 : 30 str/min (CB) imageRUNNER 2525i/2525 : 25 str/min (CB) imageRUNNER 2520i/2520 : 20 str/min (CB) A3: imageRUNNER 2545i/2545 : 22 str/min (CB) imageRUNNER 2535i/2535 : 22 str/min (CB) imageRUNNER 2530i/2530 : 15 str/min (CB) imageRUNNER 2525i/2525 : 15 str/min (CB) imageRUNNER 2520i/2520 : 15 str/min (CB)
Uvećanja	Zoom: 25-400%

	Fiksno: 25%, 50%, 70%, 100%, 141%, 200%, 400%
Vrijeme prve kopije	Crno-bijelo: 3.9 sek(45/35 str/min model), 5.4 sek (30/25 str/min model), 6.4 sek (20 str/min model)
Vrijeme zagrijavnja	30 sekundi
Višestruke kopije/ispisi	1 do 999 listova
Obostrano	Standardno
Težina papira	Kazeta: 64 do 90g/m ² Direktno umetanje: 64 do 128g/m ² Obostrano: 64 do 80g/m ²
Kapacitet papira	Kazeta 1: 550 listova (80g/m ²), (250 listova za imageRUNNER 2520i/ 2520) Kazeta 2: 550 listova za imageRUNNER 2525/i, 2530/i, 2535/i, 2545/i. 50 omotnica (uz opcionalni Envelope Feeder Attachment-D1) Direktno umetanje: 100 listova (A4,A4R,A5;80g/m ²), 50 listovaa(A3;80g/m ²) Opcionalno: 550 listova x 2 kazete (80g/m ²) 550 listova x 1 kazeta samo za imageRUNNER 2520/2520i Paper Deck: Nema Ukupan kapacitet: 2,300 listova (2,000 listava za imageRUNNER 2520i/ 2520)
CPU	Canon Custom Processor, 400MHz
Memorija	512MB (imageRUNNER 2500 i modeli), 256MB (imageRUNNER 2500 modeli bez oznake "i")
Hard Disk	Nema
Sučelje	Ethernet (100Base-TX/10Base-T), USB Host I/F 2.0 x 1 port, USB Device 1.0 x 1 port 220-240V AC, 50/60Hz, 4.2A (45/35 str/min model), 220-240V AC, 50/60Hz, 3.3A (35/30/20 str/min model))
Napajanje	220-240V AC, 50/60Hz, 4.2A (45/35 str/min model)), 220-240V AC, 50/60Hz, 3.3A (35/30/20 str/min model))
Potrošnja	1.827kW (45/35 str/min model)), 1.345kW (30/25 str/min model)), 1.542kW (20ppm str/min model))
Dimenzije	imageRUNNER 2545i/ 2545/ 2535i/ 2535 : 565 mm x 680 mm x 806 mm (sa običnim poklopcem) 565 mm x 689 mm x 907mm (sa DADFom) imageRUNNER 2530i/ 2530/ 2525i/ 2525 :

	565 mm x 680 mm x 806 mm (uz običan poklopac) 565 mm x 689 mm x 896 mm (sa DADFom) imageRUNNER 2520i/ 2520 : 565 mm x 680 mm x 681 mm (uz običan poklopac) 565 mm x 689 mm x 771 mm (sa DADFom)
Težina	imageRUNNER 2545i/2535i : cca. 78.4 kg, imageRUNNER 2545/2535: cca. 70.5 kg imageRUNNER 2530i/2525i : cca. 77.5 kg, imageRUNNER 2530/2525: cca. 68.0 kg imageRUNNER 2520i : cca. 56.0 kg, imageRUNNER 2520: cca. 50.5 kg
Network Printer Kit	
PDL	UFR II-LT, PCL5e/6 (standard na "i" modelima, opcionalno na ne "i" models), PostScript level 3 emulacija (opcija)
Rezolucija	600 x 600dpi, 1200dpi x 1200dpi (samo UFR II-LT)
Memorija	512MB (imageRUNNER 2500 serija i modeli), 256MB (imageRUNNER 2500 standard na "i")
Hard disk	Nema
CPU	Canon Custom Processor, 400MHz
PS Fontovi	Roman 136
PCL Fontovi	Roman 93
Podržani OS	PCL: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7 Postscript level 3 emulation: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7, Mac OS X (10.4 or later) UFR II-LT: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7, Mac OS X (10.4 or later), Linux Mac-PPD: Mac OS X 10.4 or later
Sučelje	Ethernet (100Base-TX/10Base-T)
Mrežni protokol	TCP/IP (LPD/ Port9100, HTTP), SMB, SNMP v1, WSD, IPv4/ IPv6 podrška
Pull Scan	Network TWAIN Driver (75/ 100/ 150/ 200/ 300dpi 8bit color / 75-600dpi 1bit crno-bijelo)
Universal Send Kit	
Opcionalno/Standardno	CLR SEND KIT-Y1 (standard na "i" modelima, opcija na ne "i" modele)
Brzina	A4, 300dpi, BW/Color: 45/34 ipm (45/ 35 str/min modeli), 25/13ipm (30/ 25/ 20 str/min modeli)
Rezolucija skeniranja	BW: 100 x 100 dpi, 150 x 150 dpi,

	200 x 100dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi CL:100 x 100 dpi, 150 x 150 dpi, 200 x 200 dpi, 300 x 300dpi
Destinacije	E-Mail/ Internet FAX(SMTP), PC/Server (SMB,FTP), iWDM, USB memorijski stick
Adresar	Lokalno (max. 500)
Format datoteke	TIFF, JPEG, PDF, High compression PDF Searchable PDF (opcija uz SEARCHABLE PDF-C1)

DADF

Opcionalno/Standardno	DADF-AA1 opcija za imageRUNNER 2545/2535, standard za imageRUNNER 2545i/2535i. DADF-AB1 opcija za imageRUNNER 2530/2525/2520, standard za imageRUNNER 2530i/2525i/2520i
Veličina papira	imageRUNNER 2545/2535: A3, A4, A4R, A5, A5R imageRUNNER 2530/2525/2520: A3, A4, A4R, A5, A5R Nestandardna veličina 139.7 do 297mm x 182 do 432mm
Težina papira	imageRUNNER 2545/2535: Jednostrani original: 42 do 128 g/m2 Obostrani original: 50 do 128 g/m2 imageRUNNER 2530/2525/2520: Jednostrani original: 37 do 128 g/m2 Obostrani original: 50 do 128 g/m2
Max. broj originala	imageRUNNER 2545/2535: listova 100 (A4, A4R, A5, A5R: 80 g/m2), 50 listova (A3: 80 g/m2) imageRUNNER 2530/2525/2520: 50 listova (A4, A4R, A5, A5R: 80 g/m2), 25 listova (A3: 80 g/m2)
Brzina skeniranja dokumenata	imageRUNNER 2545/2535: Kopiranje: 45ipm (A4, 600 x 600 dpi: BW) Skeniranje: 45/34 ipm (A4, 600 x 600 dpi: BW / 300 x 300 dpi: Colour) imageRUNNER 2530/2525/2520: Kopiranje: 25ipm (A4, 600 x 600 dpi: BW) Skeniranje: 25/13 ipm (A4, 600 x 600 dpi: BW / 300 x 300 dpi: Colour)
Dimenzije	imageRUNNER 2545/2535: 565 mm x 540 mm x 137 mm imageRUNNER 2530/2525/2520: 565 mm x 544 mm x 126 mm
Težina	imageRUNNER 2545/2535: cca. 7.9 kg imageRUNNER 2530/2525/2520: cca. 7.0 kg

cassette Feeding Module	
Ime modela	CASSETTE UNIT-W1 for imageRUNNER 2520/i CST. Feeding UNIT-AE1 za sve modele
Tip	CASSETTE UNIT-W1: Prednje podesive ladice CST. Feeding UNIT-AE1: 2 prednje podesive ladice
Težina papira	CASSETTE UNIT-W1: 64 do 90g/m ² CST. Feeding UNIT-AE1: 64 do 90 g/m ²
Kapacitet papira	CASSETTE UNIT-W1: 550 listova (80 g/m ²) x 1 cassette CST. Feeding UNIT-AE1: 550 listova (80 g/m ²) x 2 kazete
Dimenzije (Š x D x V)	CASSETTE UNIT-W1: 565 mm x 680 mm x 97 mm CST. Feeding UNIT-AE1: 565 mm x 680 mm x 248 mm
Težina	CASSETTE UNIT-W1: cca. 12.8kg CST. Feeding UNIT-AE1: cca. 24.0kg
Finišer	
Opcionalno/Standardno	Opcionalni interni Finisher-B1 za sve modele
Broj odlagača	Jednostruki odlagač (opcionalni drugi odlagač; INNER FIN ADD. TRAY-B1)
Kapacitet odlagača	A4 - A5R :1000 listova (ili 125 mm u visinu) A3, A4R: 500 listova (ili 62.5 mm u visinu)
Pozicija klamanja	Kut, dvostruko
Kapacitet klamanja	A4: 50 listova x 30 kompleta A4R/ A3: 30 listova x 15 kompleta
Unutarnji 2 Way Tray	
Kapacite odlagača	Odlagač A - A4: 250 listova , A3: 100 listova Odlagač B - A4:100 listova, A3: 50 listova
Težina	cca. 0.6kg
Ostala dodatna oprema	
Ostala dodatna oprema (opcije)	Platen Cover Type P: Platen cover - pri konfiguraciji imageRUNNER 2525/2530 bez DADF Platen Cover Type Q: Platen cover pri konfiguraciji imageRUNNER 2535/2545 bez DADF Stamp Ink Cartridge-C1: Stamp Ink Cartridge Stamp unit-B1: jedinica za pečate ADF Access Handle-A1:priključuje se na dodavač dokumenata, čime je omogućena dostupnost korisnicima u sjedećem položaju PCL Printer Kit-AF1: Podržava PCL5e i PCL6 ispis za ne "i" modele PS Printer Kit-AF1: podržava PostScript Level

3 Emulation ispis

Barcode Printing Kit-B1: omogućava ispis
barkodova pomoću Jet Caps tehnologije
Super G3 Fax Board-AG1: dodaje funkcije
telefaksa

FL Cassette-AJ1: Dodatni 550-listni odlagač
za kazetu "1" ili imageRUNNER

2525/2525i/2530/3530i/2535/2535i/2545/2545i

FL Cassette-AK1: Dodatni 550-listni odlagač
za kazetu "2" na imageRUNNER

2525/2525i/2530/3530i/2535/2535i/2545/2545i

ili za Cassette Feeding Unit-AE1 ili Cassette
Module-W1 dozvoljava zamijenu veličina
papira bez promijene postavki pisača

FL Cassette-AL1: Dodatni 250-listni odlagač
za kazete "1" ili imageRUNNER 2520/2520i
dozvoljava vam zamijenu veličina papira bez
promijene postavki pisača

Cassette Spacer-A1: Prilagođuje visinu za
250-listnu kazetu kada se kombinira sa
opcionalnom kazetom Cassette Feeding Unit-
AE1 ili Cassette Module-W1 samo za
imageRUNNER 2520/2520i

Envelope Feeder Attachment-D1: Attaches to
cassette "2" for easy envelope feeding
imageRUNNER 2500 Plain Pedestal:

Zamjensko postolje za jedinicu sa
kazetamafeeding unit and raises the device,
2 Way Unit-B1: Unaprijeđuje produktivnost
obostranog ispisa za 100%

Reversal Pass Unit(2-Way Unit) opcija za
imageRUNNER 2520/2520i/2525/2530

Staple-J1: Klamerica za interni Inner Finisher-
B1

Document Tray-J1: Ručni odlagač koji se
montira sa strane uređaja i pruža lokaciju za
odlaganje originala

Power Supply Unit-U1: jedinica za napajanje.

Card Reader Attachment-D3: Attachment kit
for Card Reader-E1

Canon Card Reader-E1: fizički pristup sustavu
koji ograničava korištenje uređaja samo na
autorizirane korisnike

USB Application 3-Port Interface Kit-A1: 3-
Port USB interface kit za USB memoriju

CCVI I/F Cable-A1: Interface Kit za Coin-
Vender

C-EXV33 TONER BK: Toner za
imageRUNNER

2520/2520i/2525/2525i/2530/2530i

C-EXV32 TONER BK: Toner za
imageRUNNER 2535/2535i/2545/2545i